

SEAT DIMENSIONS CHART



	PART NUMBER	NAME	MATERIAL	HOM OL #	SIZE	LOWER FIXING POINTS mm	SIDE FIXING H	B in	B mm	A in	A mm	E in	E mm	O in	O mm	D in	D mm	C in	C mm	F in
Com	008231	SPRINT	Steel	FIA	M	271 x 345	11.42	17.9	450	13.7	345	20.6	520	21.8	550	19.5	490	13.1	330	16.3
	008232L	SPRINT L	Steel	FIA	L	271 x 345	11.42	19.9	500	17.1	430	22.3	561	21.8	550	21.0	530	17.1	430	18.3
	008141F	REV	Fiberglass	FIA	S+M	NO	11.42	17.1	430	11.3	285	22.8	575	21.8	550	18.7	470	12.3	310	15.1
	008142F	REV II	Fiberglass	FIA	M+L	NO	11.42	18.5	467	12.5	315	23.2	585	22.2	560	21.0	530	13.1	330	17.1
	008071F	EVO	Fiberglass	FIA	M	NO	11.42	18.3	460	10.7	270	24.2	610	23.4	590	20.6	520	12.7	320	15.9
	008281F	EVO II	Fiberglass	FIA	M+L	NO	11.42	17.5	440	11.1	280	23.4	590	24.6	620	21.2	535	13.1	330	16.7
	008361F	EVO III	Fiberglass	FIA	XL	NO	11.42	20.2	510	11.9	300	25.6	645	23.8	600	22.6	570	13.9	350	17.1
	008441F	EVO II -US	Fiberglass	FIA	L	NO	11.42	18.8	473	11.7	295	23.8	600	23.8	600	21.2	533	15.6	393	17.9
	008082F	PRO 2000	Fiberglass	FIA	M	271 x 345	11.42	18.8	473	12.4	312	23.4	590	23.0	580	19.5	490	13.1	330	15.9
	008272F	PRO 2000-2	Fiberglass	FIA	M	271 x 345	11.42	19.1	480	13.3	335	23.4	590	23.0	580	19.5	490	14.3	360	17.1
	008802	GRID-2	Fiberglass	FIA	M	NO	11.42	18.8	473	12.4	312	23.4	590	23.0	580	19.5	490	13.1	330	15.9
	008062F	CIRCUIT	Fiberglass	FIA	M	NO	11.42	17.9	450	10.3	260	23.0	580	23.0	580	19.1	480	11.9	300	15.5
	008132F	CIRCUIT II	Fiberglass	FIA	M+L	NO	11.42	18.3	460	12.3	310	23.4	590	23.0	580	18.7	470	13.1	330	16.3
	008090F	PRO ADV	Fiberglass	FIA	M+L	NO	11.42	18.5	465	12.7	320	25.0	630	23.0	580	19.1	480	13.1	330	15.9
	00809Z	PRO ADV carbon	Carbon	FIA	M+L	NO	11.42	18.5	465	12.7	320	25.0	630	23.0	580	18.7	470	13.1	330	15.9
	008092F	PRO ADV TS	Fiberglass	FIA	M+L	NO	11.42	18.5	465	12.7	320	25.0	630	23.0	580	19.1	480	13.1	330	15.9
	008721 NR2	ERGO-1	Fiberglass	FIA	M	NO	11.42	19.5	490	12.8	323	22.8	575	23.6	595	19.9	500	13.5	340	16.5
008721 NR3	ERGO-2	Fiberglass	FIA	L	NO	11.42	20.2	510	13.5	340	23.8	600	25.4	640	20.6	520	14.7	370	17.1	
Road	00917	F200	Steel	/	M	271 x 345	NO	17.6	447	14.0	356	20.4	518	21.3	541	19.0	483	14.8	376	16.3
	00954	FIGHTER	Fiberglass	/	M+L	271 x 345	NO	18.8	478	11.3	287	23.8	605	25.0	635	20.0	508	14.6	371	15.9
	00965	R333	Steel	/	L	271 x 345	NO	19.9	500	11.1	280	20.6	520	24.6	620	21.0	530	14.3	360	17.5
	00959CR	CHRONO ROAD [L]	Steel	/	L	271 x 345	NO	21.0	533	12.0	305	22.5	572	26.5	673	21.0	533	14.5	368	17.9
	00959CRM	CHRONO ROAD [M]	Steel	/	M	271 x 345	NO	20.0	508	12.0	305	22.5	572	26.5	673	20.0	508	13.5	343	17.5
	00961	R100	Steel	/	M+L	271 x 345	NO	19.7	500	13.0	330	20.5	521	27.7	704	19.6	498	14.5	368	17.5
	00968	R600	Steel	/	M	271 x 345	NO	19.3	490	10.6	269	22.1	561	22.3	566	19.2	488	13.1	333	17.5
	00974	SPX	Carbon	/	M+L	271 x 345	NO	18.5	470	11.0	279	21.0	533	26.3	667	18.5	470	12.0	305	/

F mm	G in	G mm	M in	M mm	I in	I mm	N in	N mm	S in	S mm	SHELL KG	LBS W/CVR
410	20.6	520	34.1	860	4.4	110	/	/	/	/	/	19.3
460	21.8	550	35.7	900	3.2	80	/	/	/	/	/	30.5
380	20.2	510	34.5	870	4.8	120	/	/	17.9	450	6.60	18.0
430	20.2	510	37.3	940	4.8	120	/	/	/	/	7.90	20.9
400	19.9	500	35.3	890	4.8	120	/	/	20.2	510	6.60	18.0
420	20.2	510	36.3	915	6.4	160	/	/	/	/	7.70	20.5
430	20.2	510	34.7	875	4.8	120	/	/	/	/	6.90	18.7
450	19.5	490	35.1	884	3.8	95	/	/	/	/	6.70	18.3
400	21.2	535	35.7	900	4.6	115	/	/	20.2	510	6.90	18.7
430	19.9	500	35.7	900	4.8	120	/	/	/	/	6.70	18.3
400	21.2	535	35.7	900	0.4	10	/	/	20.2	510	7.20	19.4
390	21.8	550	36.9	930	4.4	110	20.2	510	16.3	410	7.45	19.9
410	21.0	530	37.3	940	4.8	120	26.2	660	17.5	440	7.83	20.8
400	21.0	530	36.9	930	4.8	120	19.5	490	21.4	540	10.00	25.5
400	21.0	530	36.9	930	4.8	120	19.5	490	15.1	380	5.30	15.2
400	21.0	530	36.9	930	4.8	120	16.3	410	12.3	310	7.50	20.0
415	22.4	565	38.1	960	2.4	60	18.7	470	/	/	7.90	20.9
430	23.8	600	40.5	1020	2.4	60	18.7	470	/	/	11.80	29.5
410	20.1	511	34.1	866	4.8	121	/	/	17.9	450	/	18.7
400	19.8	503	34.5	876	na	na	/	/	/	/	/	21.9
440	23.4	590	36.5	920	na	na	/	/	/	/	/	31.6
450	21.5	546	36.5	927	na	na	/	/	/	/	/	33.0
440	21.5	546	36.5	927	na	na	/	/	/	/	/	32.5
440	21.0	533	36.7	932	na	na	/	/	/	/	/	30.8
440	24.0	610	35.4	899	na	na	/	/	18.5	465	/	34.6
/	24.0	610	39.0	991	na	na	/	/	/	/	/	28.0

