

${\bf Additional\ product\ information,\ including\ Product\ Data\ Sheets\ and\ this\ chart,\ is\ available\ at\ mobiloil.com}$

Updated: March 2017

Opuateu. Waren		Nominal Phosphorus	Nominal Zinc Level,		Recommended	API, ILSAC, and Other Industry	ACEA	GM Service	Ford Service Fill	МВ	BMW	vw
Brand Name	Viscosity	Level, PPM	PPM	Product Description	Consumer Applications	Approvals***	Approvals	Fill Approval	Approval	Approval	Approval	Approval
Mobil 1™ Annual Protection	0W-20	650	750	Ultimate full synthetic, our latest technology, controls breakdown to extend oil life, providing ExxonMobil's longest lasting, guaranteed engine protection.	Most vehicles that specify 0W-20 (newer Toyotas, Hondas, & GMs), 5W-20 and certain hybrids.	GF-5, SN		dexos 1	x			
Mobil 1™ Annual Protection	5W-20	800	900	Ultimate full synthetic, our latest technology, controls breakdown to extend oil life, providing ExxonMobil's longest lasting, guaranteed engine protection.	Vehicles that require 5W- 20.	GF-5, SN		dexos 1	x			
Mobil 1™ Annual Protection	5W-30	800	900	Ultimate full synthetic, our latest technology, controls breakdown to extend oil life, providing our longest lasting, guaranteed engine protection.	Vehicles that require 5W- 30 or 10W-30.	- GF-5, SN Honda HTO-06	A1/B1	dexos 1	x			
Mobil 1™ Extended Performance	0W-20	650	750	Boosted, advanced full synthetic formula designed for today's longer oil change intervals in many domestic, including GM, and imported vehicles.	Most vehicles that specify 0W-20 (newer Toyotas, Hondas, & GMs), 5W-20 and certain hybrids.	GF-5, SN		dexos 1	x			
Mobil 1™ Extended Performance	5W-20	800	900	Boosted, advanced full synthetic formula designed for today's longer oil change intervals in many domestic, including GM, and imported vehicles.	Vehicles that require 5W-20.	GF-5, SN		dexos 1	Х			
Mobil 1™ Extended Performance	5W-30	800	900	Boosted, advanced full synthetic formula designed for today's longer oil change intervals in many domestic, including GM, and imported vehicles.	Vehicles that require 5W- 30 or 10W-30.	- GF-5, SN Honda HTO-06	A1/B1	dexos1	X			
Mobil 1™ Extended Performance	10W-30	800	900	Boosted, advanced full synthetic formula designed for today's longer oil change intervals in many domestics and imports.	Vehicles that require 10W-30.	GF-5, SN	A1/B1					



${\bf Additional\ product\ information,\ including\ Product\ Data\ Sheets\ and\ this\ chart,\ is\ available\ at\ mobiloil.com}$

Updated: March 2017

opuateu: March	2017											
		Nominal	Nominal			API, ILSAC, and			Ford			
		Phosphorus	Zinc Level,		Recommended	Other Industry	ACEA	GM Service	Service Fill	MB	BMW	vw
Brand Name	Viscosity	Level, PPM	PPM	Product Description	Consumer Applications	Approvals***	Approvals	Fill Approval	Approval	Approval	Approval	Approval
					Most vehicles that							
	0W-20			Advanced full synthetic	specify 0W-20 (newer							
	Advanced			formulation designed for	Toyotas, Hondas, &							
	Fuel			enhanced fuel economy and cold	GMs), 5W-20 and							
Mobil 1™	Economy	650	750	weather performance.	certain hybrids.	GF-5, SN		dexos 1	Х			
	0W-30			Advanced full synthetic								
	Advanced			formulation designed for	Most vehicles that							
	Fuel			enhanced fuel economy and cold								
Markil ATM		CEO	750	·	' '	CE E CNI	A 1 /D1	da	V			
Mobil 1™	Economy	650	750	weather performance.	30.	GF-5, SN	A1/B1	dexos 1	Х			
				Advanced full synthetic	Many European							
				formulation designed to meet	vehicles.							
				the requirements of many	For high HT/HS					229.3 /		502.00 /
Mobil 1™ FS	0W-40	1000	1100	European vehicles.	applications.	SN, Porsche A40	A3/B3, A3/B4			229.5		505.00
				Advanced full synthetic								
				formulation designed to meet								
				the requirements of many newer								
				vehicles including Hondas, Fords,	•							
Mobil 1 [™]	5W-20	800	900	Chryslers and newer Toyotas. Advanced full synthetic	20.	GF-5, SN		dexos 1	Х			<u> </u>
				formulation designed to meet								
				the requirements of many								
				domestic, including GM, and	Vehicles that require 5W	GE 5 SN Honda						
Mobil 1™	5W-30	800	900	imported vehicles.	30. Corvette approved.	HTO-06	A1/B1	dexos1	Х			
IVIODII I	3W-30	800	300	imported verilicies.	50. Corvette approved.	1110-00	AI/DI	uex031	^			
				Higher viscosity, advanced full								
				synthetic formula designed for	Porsche. For high HT/HS					229.1 /		
Mobil 1™ FS X2	5W-50	1000	1100	performance vehicles.	applications.	SN, Porsche A40	A3/B3, A3/B4			229.3		
				Advanced full synthetic formula								
				designed for domestics and	Vehicles that require							
Mobil 1™	10W-30	800	900	imports.	10W-30.	GF-5, SN	A1/B1					
				Boosted, higher viscosity,		·	·					
				advanced full synthetic formula	For high HT/HS							
				designed for performance	applications. Racing and							
Mobil 1™	15W-50	1200	1300	vehicles.	Flat tappet applications.	SN	A3/B3					<u> </u>
						CKA CIA CIA						
				Advanced full conthetic ferresula	Most dissal appliesting	CK-4, CJ-4, CI-4,						
Mahil 1M Turk				T	Most diesel applications.	CI-4 Plus, SN,						
Mobil 1™ Turbo	EVA/ 40	1100	1300	designed for diesel powered pick-		Caterpillar ECF-2						
Diesel Truck	5W-40	1100	1300	ups and trucks.	diesel particulate filters.	and ECF-3	E7, E9	l	L			<u> </u>



 ${\bf Additional\ product\ information,\ including\ Product\ Data\ Sheets\ and\ this\ chart,\ is\ available\ at\ mobiloil.com}$

Updated: March 2017

Updated: March												
Brand Name	Viscosity	Nominal Phosphorus Level, PPM	Nominal Zinc Level, PPM	Product Description	Recommended Consumer Applications	API, ILSAC, and Other Industry Approvals***	ACEA Approvals	GM Service Fill Approval	Ford Service Fill Approval	MB Approval	BMW Approval	VW Approval
				Boosted, advanced full synthetic								
Mobil 1™ High				formula designed for higher								
Mileage	0W-20	800	900	mileage vehicles.		SN						
				Boosted, advanced full synthetic								
Mobil 1™ High				formula designed for higher	Vehicles that require 5W-							
Mileage	5W-20	800	900	mileage vehicles.	20.	SN	A1/B1					
	311 20	000	300	Timeage vermeres:		5.1	7.1,51					
				Boosted, advanced full synthetic								
Mobil 1™ High				formula designed for higher	Vehicles that require 5W-							
Mileage	5W-30	800	900	mileage vehicles.	30 or 10W-30.	SN	A1/B1					
				Boosted, advanced full synthetic								
Mobil 1™ High				formula designed for higher	Vehicles that require							
Mileage	10W-30	800	900	mileage vehicles.	10W-30.	SN	A3/B3					
				Boosted, advanced full synthetic								
Mobil 1™ High				formula designed for higher	Higher viscosity		/					
Mileage	10W-40	800	900	mileage vehicles. Advanced full synthetic formula	applications.	SN	A3/B3					
				designed specifically for	Low SAPS.					229.31 /		
Mobil 1™ ESP				passenger car diesels that have	Available at most MB					229.51 /		
X1	0W-30	800	900	particulate filters.	dealers.		C3, C2			229.52		
7.2	011 33	333	300	particulate interes	a careror	SN, Porsche C30,	03, 02			223.52		
						Chrysler MS-						
				Advanced full synthetic formulas		11106, PSA						
				designed specifically for		B712290, PSA						
Mobil 1™ ESP				passenger car diesels that have		B712297, JASO				229.31/		504.00 /
Formula	5W-30	800	900	particulate filters.	Low SAPS.	DL-1	C3, C2	dexos2		229.51	Longlife-04	507.00
				Advanced full synthetic formulas designed specifically for								
Mobil 1				motorcycles where clutch	All motorcycles where	JASO MA 2011,						
Racing™ 4T	10W-40	1100	1200	lubrication is also important.	10W-40 is specified.	MA2 2011						
				Advanced full synthetic formulas	All motorcycles where							
				designed specifically for	20W-50 is specified,							
Mobil 1™ V-				motorcycles where clutch	especially V-Twin							
Twin	20W-50	1600	1750	lubrication is also important.	engines.	SJ						
I WILL	2000-30	1000	1730	Advanced full synthetic formula	ciigiiics.	- 33						
				specifically designed to maximize	Race engines. Not							
Mobil 1				horsepower under race	recommended for street							
Racing™	0W-30	1750	1850	conditions.	use.							
				Advanced Cill and balls C								
				Advanced full synthetic formula	Daga anginas Nat							
N 4 - la:1 1				specifically designed to maximize	•							
Mobil 1	014/ 50	1750	1950	engine protection under race	recommended for street							
Racing™	0W-50	1750	1850	conditions.	use.						1	

^{***}For a full list of industry and original equipment manufacturer approvals by product and viscosity, see the Product Data Sheets available online at mobiloil.com