

**BluePrint Engines**  
 1.800.483.4263  
 www.biueprintengines.com

**DYNOMite Test Run:** PSLS4272CTF 302437

**Date:** 5/13/2014

**Correction Method:** Standard

**Notes:** PSLS4272CTF 302437

RPM (RPM)	Hp (Hp)	Torque (ft-lb)	E-Temp (Degree F)	PSI-4 B1 (PSI)	Humid (%)
2800	270.8	500.2	176	60.35	20.39
2900	276.4	503.5	176	60.63	20.37
3000	292.5	513.2	176	61.44	20.34
3100	308.1	522.4	176	62.27	20.32
3200	323.2	530.5	176	63.09	20.31
3300	338.0	537.9	176	63.88	20.29
3400	352.8	544.3	176	64.66	20.27
3500	366.2	548.7	176	65.44	20.25
3600	377.7	550.8	176	66.19	20.24
3700	388.4	551.5	176	66.94	20.22
3800	399.0	551.9	176	67.62	20.21
3900	410.0	552.7	176	68.26	20.20
4000	422.0	554.8	176	68.97	20.19
4100	435.5	558.2	176	69.75	20.18
4200	449.7	562.5	176	70.53	20.18
4300	463.9	566.8	176	71.27	20.17
4400	478.2	570.7	176	72.00	20.17
4500	491.4	573.2	176	72.71	20.17
4600	503.3	574.1	176	73.40	20.17
4700	513.3	573.2	176	73.99	20.17
4800	522.2	571.1	176	74.54	20.16
4900	531.7	569.8	176	75.10	20.16
5000	542.8	570.1	176	75.67	20.16
5100	554.8	571.1	176	76.20	20.16
5200	566.4	571.8	176	76.71	20.16
5300	577.1	571.4	176	77.28	20.15
5400	585.3	568.4	176	77.72	20.15
5500	589.5	563.5	176	78.00	20.14
5600	593.5	557.5	176	78.35	20.13
5700	598.9	552.2	176	78.70	20.12
5800	604.6	547.5	176	79.04	20.11
5900	610.4	543.6	176	79.41	20.10
6000	616.0	539.0	176	79.67	20.09
6100	618.7	532.4	176	79.80	20.08
6200	616.8	521.7	176	79.77	20.07