



## Mobil 1 ESP Formula 0W 40

Mobil Passenger Vehicle Lube, United States

Fully Synthetic Engine Oil

### Product Description

Mobil 1™ ESP Formula 0W-40 is a fully synthetic engine oil designed to help provide exceptional cleaning power, wear protection and overall performance. Mobil 1 ESP Formula 0W-40 has been expertly engineered to help prolong the life and maintain the efficiency of emission systems in both diesel and gasoline powered automobiles.

### Features and Benefits

Mobil 1 ESP Formula 0W-40 is made with a proprietary blend of leading edge components formulated to be fully compatible with the latest Diesel Particulate Filters (DPF's) and Gasoline Catalytic Converters (CAT's). Mobil 1 ESP Formula 0W-40 has been designed to help deliver outstanding performance and protection in conjunction with potential fuel economy benefits. Key features and potential benefits include:

<b>Features</b>	<b>Advantages and Potential Benefits</b>
Low Ash Content	Helps to reduce particulate build up in Diesel Particulate Filters
Low Sulphur and Phosphorous content	Helps to reduce poisoning of Gasoline Catalytic Converters
Active cleaning agents	Helps to reduce deposits and sludge build-up to enable long and clean engine life
Outstanding thermal and oxidation stability	Helps to reduce oil aging allowing extended drain interval protection
Low oil consumption	Less hydrocarbon pollution

<b>Features</b>	<b>Advantages and Potential Benefits</b>
Enhanced frictional properties	Potentially aids fuel economy
Excellent low temperature capabilities	Quick cold weather starting and ultra fast protection Helps to extend engine life

## Applications

Mobil 1 ESP Formula 0W-40 has the General Motors Service Fill dexos2™ approval, which is required for all 2010 and onward new GM/Opel/Vauxhall/Chevrolet Diesel and Gasoline models. GM/Opel have advised that dexos2™ specification is backward compatible to older GM/Opel specifications (GM-LL-A-025 and GM-LL-B-025). The majority of GM/Opel/Vauxhall/Chevrolet Diesel and Gasoline vehicles can use dexos2™ lubricants.

Mobil 1 ESP Formula 0W-40 is especially suitable for extreme conditions, where conventional oil often may not perform.

It is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

## Specifications and Approvals

<b>Mobil 1 ESP Formula 0W-40 has the following builder approvals:</b>	
General Motors Service Fill	dexos2™ (license number D20679HJ015))

## Typical Properties

<b>Mobil 1 ESP Formula 0W-40</b>	
----------------------------------	--

<b>Mobil 1 ESP Formula 0W-40</b>	
Viscosity, ASTM D 445	
cSt @ 40°C	69
cSt @ 100°C	12.9
Sulfated Ash, wt%, ASTM D 874	0.8
Phosphorous	0.09
Flash Point, °C, ASTM D 92	232
Density @ 15° C kg/l, ASTM D 4052	0.8408
Total Base Number (TBN) ASTM D 2896	8.5
MRV at -40°C	20100
Viscosity Index	189
HTHS Viscosity, mPa•s @ 150°C, ASTM D 4683	3.53

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment.

Mobil, Mobil 1 and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

01-2018

**Exxon Mobil Corporation**

22777 Springwoods Village Parkway

Spring TX 77389

1-800-ASK MOBIL (275-6624)

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)*

*ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.*

© Copyright 2003-2017 Exxon Mobil Corporation. All Rights Reserved.