



World's Finest Automotive Bra

Installation Instructions: C6 Corvette Nosecover

Parts Included - Two (2) Universal-sided FasTrak mounting brackets, adhesive hook-tape

Required Tools - ¼" ratchet, 7mm or 5/16 socket, flat-blade screwdriver, scissors

Required Cleaning Supplies - wax/polish, vinyl dressing, clean rags

Pre Installation

- 1) Carefully read and follow instructions to ensure optimal performance
- 2) Thoroughly wash & wax vehicle surfaces including inside wheel wells and under front bumper, to prevent entrapment of moisture and/or debris between paint finish and *SpeedLingerie™*.
- 3) Place unfolded *SpeedLingerie™* in direct sunlight, or near (but not in direct contact with) any radiant heat source for 20-30 minutes to warm-up the *SpeedLingerie™*. Park the car in direct sunlight to warm-up the front-end surface.
NOTE! Warming the *SpeedLingerie™* and the vehicle front-end will make the *SpeedLingerie™* more flexible and easier to install.
- 4) Orient yourself with *SpeedLingerie™*. Notice placement correlation of mesh and grills.
- 5) For easier access to wheel well area, turn the steering wheel to the passenger side.

FasTrak Bracket Installation

- 1) Start on the driver side. **Note:** There are (5) re-useable plastic pop-rivet fasteners that hold the wheel well liner to the fender. You will remove only the top (4) fasteners. You will not remove the bottom-most fastener at the spoiler
- 2) Use a flat blade screwdriver to pop-up the center section of the pop-rivet about 3/8" (It is OK if the center section comes all the way out).
- 3) Next use your fingernails or the screwdriver to remove the outer section of the pop-rivet from the hole.
- 4) Remove any protective film from a bracket.
- 5) Orient the bracket with the straight-edge inward, and the tab-end down. Align the *FasTrak™* bracket with the wheel well surface and pop-rivet holes.
- 6) To re-install each pop-rivet, press the outer section of the pop-rivet through bracket and wheel well first. Then press-in the center section to lock the pop-rivet
- 7) Repeat step #6 for the remaining (3) pop-rivets on the driver side.
- 8) At the passenger side, repeat steps #1-7.

Top Edge Hook-Tape Installation

- 1) Open the hood.
- 2) **Note:** With the hood in the "up" position, there are (4) screws just inside the top edge of the nose.
- 3) Use the 7mm or 5/16" socket and ratchet to removed all (4) screws.
- 4) Install the adhesive backed hook-tape to the surface where the screws are located.
- 5) Re-install and securely fasten the screws.

SpeedLingerie Nose Cover Installation

- 1) Open the hood.
- 2) Face the front of the vehicle. Hold the properly oriented *SpeedLingerie™* outstretched in front of you.
- 3) Attach the top edge of the Nose Cover to the hook-tape you installed in "*Top Edge Hook-Tape Installation*", so the *SpeedLingerie™* hangs in place.
- 4) Guide the (4) tongue panels at the bottom inside of the *SpeedLingerie™* through the grill.
- 5) Underneath the front end attach the *QuiKlip™* at the ends of the (4) tongue panels to the *QuiKlip™* sewn into the bottom edge of the spoiler.
- 6) Adjust the bottom edge of the mesh so it is about 2" inside of the lower leading edge of the chin.
- 7) At the passenger side, run your thumb through the *QuiKlip™* to "open it up" slightly. This will help you to clip the fastener on the wheel well edge. **NOTE!** Enfold (using a key or credit card or business card) the 5-inch quick release strap within the molded fastener. This ensures easy removal of *SpeedLingerie™*. Do not pull on this strap during installation.
- 8) Clip the bottom portion of the *QuiKlip™* fastener onto the top edge of the FasTrak and work your way down.
- 9) **NOTE!** Due to the perfectly tailored fit of *SpeedLingerie™*, step#9 takes careful effort. Acquire assistance, to provide "slack" from the front-end midpoint. Do not pull on the molded fastener/stitching itself. Do not pull from the top edge. Installation becomes easier with repeated use.

Welcome to the SpeedLingerie team!

You've joined the elite by selecting our truly custom designed and hand crafted protective accessories. Each product is created using the highest quality factory color matched materials, tri-layer construction with a moisture wicking internal layer, durable and elegant French seams, and cleverly engineered patent pending designs, light shields and non-metallic FasTrak™ and QuiKlip™ fastening systems. SpeedLingerie.com, Inc.'s custom products are speed rated to provide flap-free protection at speeds up to 150 mph, are fully supported with our excellent craftsmanship warranty, and come with a 30-day customer satisfaction money back guarantee*(unheard of for a custom product!).

We offer all our SpeedLingerie team members the opportunity to be seen and heard on our worldwide website www.speedlingerie.com. Submit digital images of your vehicle in SpeedLingerie at home, on the road, or at a club event for posting on the Gallery, or give your feedback for the Testimonial page; email info@speedlingerie.com.

Take the time to read the installation instructions and warranty, and send the completed warranty application back to us. We're always happy to provide installation assistance or answer any questions; call us toll-free (800) 570-1579 or dial direct (650) 964-2584 Monday through Friday, 9am – 5pm (PST).

From all of us at SpeedLingerie.com, Inc.,
Thanks and welcome aboard!

The logo for SpeedLingerie features the word "SPEED" in a large, bold, blue, italicized sans-serif font. Below it, the word "LINGERIE" is written in a smaller, blue, all-caps sans-serif font. To the right of "LINGERIE", there is a small graphic element consisting of three vertical bars of varying heights, resembling a stylized "E" or a speedometer needle.

World's Finest Automotive Bra™

*Does not apply to special orders.



World's Finest Automotive Bra

SpeedLingerie.com, Inc
 1917 Old Middlefield Way, #5
 Mountain View, CA 94043 USA
 Tel:650-964-2584 Fax:650-964-2586

Packing Slip

Date	Invoice #
10/7/2005	13909

BILL TO

PAID

SHIP TO

S.O. No.	PO #	Terms	Ship Date	VIA
305971	1284	Prepaid	10/7/2005	UPS GRD

QTY	ITEM CODE	DESCRIPTION	ORDERED	PREV. INVOICED
1	NC0640	C6 Victory Red 05 Nosecover	1	0
1	UPSgd	UPS Ground-Non Refundable	1	0

Returns - Contact SpeedLingerie.com, Inc. at (650)964-2584 to request an RMA number. All returns must be in new, undamaged, saleable condition and include a copy of packing slip/receipt. A 15% restocking fee will be charged for all items returned after 30 days from purchase date. No returned items will be accepted after 60 days from purchase date. *NO RETURNS ACCEPTED FOR CUSTOM COLORS OR MODIFICATIONS

Warranty - SpeedLingerie.com, Inc. supports product quality with a Limited Lifetime Craftsmanship Warranty. Submit warranty registration and call 1-650-964-2584 for warranty repairs.

E-mail	Web Site
sales@speedlingerie.com	www.speedlingerie.com