

(Corvette C6 – continued)

- 10) Working from the passenger side, come across the front end and carefully but firmly stretch the *SpeedLingerie™* towards the driver side. Gather 6-8" of material at the molded fastener strip in your hands, and carefully but firmly pull from the side at the midpoint and the lower corner (spoiler level). Repeat step#8 to clip the fastener on the driver side.
- 11) At the driver side, attach the small side clips (near the top) to the edges of the wheel well liner, inside the wheel well.
- 12) Repeat step#11 on the passenger side.
- 13) Re-attach and adjust the top edge of the *SpeedLingerie™*.
- 14) Attach the (2) *QuiKlips™* at the top edge of the SL onto the body (just inside the headlights).
- 15) Flip the Flat Tabs at the top edge of the *SpeedLingerie™* into the gaps just inside each headlight assy.

Mirror Cover Installation

- 1) To differentiate between passenger and driver side mirror cover, the vinyl covered loop portion of the hook & loop fastener folds **down and over the hooked portion**.
- 2) Lower/open windows. Close doors. Enjoy the opportunity to work with your car and take your time.
- 3) Begin at passenger side. Open the hook & loop tab.
- 4) Stretch out mirror cover tension cord and slip the cover over the mirror head. **NOTE!** Support the mirror head properly during installation.
- 5) Form the mirror cover into place using both hands and temporarily fasten the hook and loop tab. **NOTE!** Refer to Pre-installation Step #1 if you are unsure whether you are installing the appropriate mirror cover on the correct side.
- 6) With both hands, continue forming the mirror cover into place (like molding clay). Adjust material around face of mirror until mirror-opening edges at tension cord align and meet. You may need to open/close hook & loop tab several times during this process.
- 7) Repeat Steps # 2 – 5 at driver side.

Final Adjustment

- 1) Adjust *SpeedLingerie™* where necessary, to assure proper fit.
- 2) For full effect of *SpeedLingerie™* design and glove-like fit, allow 72 hours for material(s) to relax and conform to vehicle's curves.
- 3) Park in a warm sunny spot with *SpeedLingerie™* on for a few days, to help the process.
- 4) You may apply a quality vinyl conditioner if you so desire.

Care & Maintenance

- 1) For best results, be sure that vehicle surfaces are clean and dry before installing *SpeedLingerie™*.
- 2) Always inspect *SpeedLingerie™* fasteners and surfaces that contact vehicle for possible debris, sand, grit, etc... and remove before installation.
- 3) Periodically remove *SpeedLingerie™* to allow complete aeration of vehicle paint finish and *SpeedLingerie™* materials.
- 4) Remove *SpeedLingerie™* before washing vehicle.
- 5) Remove *SpeedLingerie™* after exposure to rain or other fluids/moisture.
- 6) Clean outer vinyl surfaces of *SpeedLingerie™* with a high quality conditioner during routine car maintenance.
- 7) Clean felt inner surface with water if necessary, allowing it to dry completely, and brush/vacuum out any remaining particles.
- 8) Rubber will stain vinyl. DO NOT store your *SpeedLingerie™* in direct contact with any rubber products (ie: tires, hoses, etc) as vinyl is a very porous material and will absorb the black carbon in rubber products, resulting in a stain on the vinyl.

Congratulations again on the purchase of your *SpeedLingerie™*.

Installation Questions? Call 1(800) 570-1579 for assistance.