



## Mobil 1™ Extended Performance

Mobil Passenger Vehicle Lube, United States

View the [Mobil 1 Extended Performance](#)  
Advanced Full Synthetic Engine Oil

### Product Description

Mobil 1™ Extended Performance 0W-20, 5W-20, 5W-30, and 10W-30 are advanced full synthetic engine oils designed to keep your engines running like new and protect critical engine parts for 15,000 miles between oil changes. Mobil 1 Extended Performance features a special formulation that helps to provide outstanding protection during today's longer oil change intervals.

### Features and Potential Benefits

Mobil 1 Extended Performance 0W-20, 5W-20, 5W-30, and 10W-30 are made with a proprietary blend of high performance synthetic basestocks fortified with a precisely balanced additive component system, designed especially to help deliver performance and protection during long service intervals. Mobil 1 Extended Performance oils are uniquely designed to help provide outstanding levels of performance, cleaning power and engine protection, even during longer oil change intervals.

Features	Advantages and Potential Benefits
Advanced Full synthetic formula	Helps to prevent deposits and sludge build-up to enable long engine life. Excellent overall lubrication and wear protection performance under many all operating conditions, from mild to severe
Precise balance of performance additives	Helps to provide outstanding engine protection at oil change intervals of up to 15,000 miles or 1 year, whichever comes first
Outstanding thermal and oxidation stability	Exceptional control of oil breakdown; Helps maintain stable oil viscosity

Provides exceptional engine protection	Helps to maintain long engine life and is compatible with engine seals
Excellent low temperature capabilities	Quick cold weather starting for fast protection and extended engine life. Helps to provide less stress on your starting system

## Applications

Mobil 1 Extended Performance engine oils are recommended for all types of modern vehicles, including high-performance turbo-charged, supercharged gasoline multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks.

- Mobil 1 Extended Performance oils provide guaranteed protection of critical engine parts for 15,000 miles or one year, whichever comes first. Excluded service includes: commercial and racing applications; frequent towing or hauling; extremely dusty or dirty conditions; or excessive idling.
- If your vehicle is covered by a warranty, follow the vehicle's oil life sensor or the oil change interval recommended in your owner's manual. Proper maintenance practices, including frequently checking the oil level to ensure that the appropriate amount of oil is present, are required to ensure effective performance.

## Specifications

Mobil 1 Extended Performance meets or exceeds the requirements of:	0W-20	5W-20	5W-30	10W-30
ILSAC	GF-5	GF-5	GF-5	GF-5
API	SN,SM,SL,SJ, SN PLUS, SN PLUS RESOURCE CONSERVING	SN,SM,SL,SJ	SN,SM,SL,SJ	SN,SM,SL,SJ
ACEA			A1/B1, A5/B5	A1/B1, A5/B5

Ford		WSS-M2C945-A	WSS-M2C946-A	
Ford	WSS-M2C947-A	WSS-M2C930-A	WSS-M2C929-A	
Ford	WSS-M2C947-B1			
Honda			HTO-06	

Mobil 1 Extended Performance has the following builder approvals:	0W-20	5W-20	5W-30	10W-30
General Motors	dexos1™ Gen 2 (License number D10105GH015)	dexos1™ Gen 2 (License number D10106GH015)	dexos1™ Gen 2 (License number D10107GH015)	

(dexos1 is a registered trademark of General Motors)

According to ExxonMobil, Mobil 1 Extended Performance is of the following quality level:	0W-20	5W-20	5W-30	10W-30
General Motors 4718M			X	X
General Motors 6094M	X	X	X	X
API CF	X	X	X	X

### Typical Properties

Mobil 1 Extended Performance	0W-20	5W-20	5W-30	10W-30
------------------------------	-------	-------	-------	--------

SAE Grade	0W-20	5W-20	5W-30	10W-30
Viscosity @ 100 °C, cSt (ASTM D445)	8.6	8.9	10.6	10.2
Viscosity, @ 40 °C, cSt (ASTM D445)	44.9	49.6	59.8	63.7
Viscosity Index	173	161	169	147
Sulfated Ash, wt% (ASTM D874)	0.8	0.8	0.8	0.8
HTHS Viscosity, mPa•s @ 150 °C (ASTM D4683)	2.7	2.75	3.0	3.1
Pour Point, °C (ASTM D97)	-54	-42	-40	-39
Flash Point, °C (ASTM D92)	235	230	230	232
Density @ 15.6 °C g/ml (ASTM D4052)	0.839	0.850	0.851	0.856

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Mobil, Mobil 1 and the Pegasus design are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

06-2018

### **Exxon Mobil Corporation**

22777 Springwoods Village Parkway  
Spring TX 77389

1-800-ASK MOBIL (275-6624)

*Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information,*