

Brand Name	Viscosity	Nominal Phosphorus Level, PPM	Nominal Zinc Level, PPM	Product Description	Recommended Consumer Applications	API, ILSAC, and Other Industry Approvals***	ACEA Approvals
Mobil 1 [®] Extended Performance	0W-20	760	830	Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect for 20,000 miles between oil changes – guaranteed.	Most vehicles that specify 0W-20 (newer Toyotas, Hondas, & GMs), 5W-20 and certain hybrids.	GF-6A, API SP, SP Resource Conserving, SN Plus, SN	
Mobil 1 [®] Extended Performance	5W-20	760	830	Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect for 20,000 miles between oil changes – guaranteed.	Most vehicles that require 5W-20.	GF-6A, API SP, SP Resource Conserving, SN Plus, SN	
Mobil 1 [®] Extended Performance	5W-30	760	830	Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect for 20,000 miles between oil changes – guaranteed.	Most vehicles that require 5W-30 or 10W-30.	GF-6A, API SP, SP Resource Conserving, SN Plus, SN, Honda/Acura HTO-06	
Mobil 1 [®] Extended Performance	10W-30	760	830	Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect for 20,000 miles between oil changes – guaranteed.	Most vehicles that require 10W-30.	GF-6A, API SP, SP Resource Conserving, SN Plus, SN	
Mobil 1 [®] Extended Performance High Mileage	0W-20	800	870	Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect vehicles with over 75,000 miles for 20,000 miles between oil changes – guaranteed.	Most vehicles that specify 0W-20 (newer Toyotas, Hondas, & GMs), 5W-20 and certain hybrids.	GF-6A, API SP, SP Resource Conserving, SN Plus, SN	
Mobil 1 [®] Extended Performance High Mileage	5W-20	800	870	Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect vehicles with over 75,000 miles for 20,000 miles between oil changes – guaranteed.	Most vehicles that require 5W-20.	GF-6A, API SP, SP Resource Conserving, SN Plus, SN	
Mobil 1 [®] Extended Performance High Mileage	5W-30	800	870	Advanced Full Synthetic motor oil, designed to maximize power in your engine and protect vehicles with over 75,000 miles for 20,000 miles between oil changes – guaranteed.	Most vehicles that require 5W-30 or 10W-30.	GF-6A, API SP, SP Resource Conserving, SN Plus, SN	
Mobil 1 [®] ESP X3	0W-40	900	990	Advanced full synthetic formula designed to help maintain the efficiency of emission systems in new emerging diesel and gasoline powered European vehicles.	High power European engines requiring high HT/HS and GPF compatibility	API SN Plus	C3
Mobil 1 [®] ESP X2	0W-20	880	950	Advanced full synthetic formula designed to help maintain the efficiency of emission systems in new emerging diesel and gasoline powered European vehicles.	Most vehicles that require 0W-20.	API SP ETR	C5 / C6
Mobil 1 [®] ESP	0W-30	800	900	Advanced full synthetic formula designed specifically for passenger car diesels that have particulate filters.	Low SAPS. Available at most MB dealers.	API SP ETR	C3
Mobil [®] 1 Supercar	0W-40	900	990	Advanced full synthetic formula designed for high performance cars to deliver outstanding overall performance.	Corvettes and Camaros that call for 0W-40 oil.		
Mobil [®] 1 Supercar	5W-50	1100	1200	Advanced full synthetic formula designed for high performance cars to deliver outstanding overall performance.	Newer Corvettes that call for 5W-50 oil.	API SP	
Mobil 1 [®] ESP	5W-30	800	900	Advanced full synthetic formula designed specifically for passenger car diesels that have particulate filters.	Low SAPS.	API SP, Fiat S3	C3
Mobil 1 [®] FS	0W-40	930	1000	Advanced full synthetic formulation designed to meet the requirements of many European vehicles.	Many European vehicles. For high HT/HS applications. High SAPS	API SP, SN Plus, SN	A3/B4
Mobil 1 [®] FS X2	5W-50	930	1000	Higher viscosity, advanced full synthetic formula designed for performance vehicles.	Many European vehicles. For high HT/HS applications. High SAPS	API SP, SN Plus, SN	A3/B4

Mobil 1 ⁺ FS	5W-40	930	1000	Advanced full synthetic formulation designed to meet the requirements of many European vehicles.	Many European vehicles. For high HT/HS applications. High SAPS	API SP, SN Plus, SN	A3/B4
Mobil 1 ⁺	0W-16 Advanced Fuel Economy	760	830	Advanced ultra-low viscosity full synthetic motor oil, engineered to enhance fuel economy and protect for 10,000 miles between oil changes – guaranteed.	Certain Toyota and Honda vehicles requiring 0W-16 oil.	GF-6B, API SP, SP Resource Conserving, SN Plus, SN	
Mobil 1 ⁺	0W-20 Advanced Fuel Economy	760	830	Advanced full synthetic motor oil, engineered to enhance fuel economy and protect for 10,000 miles between oil changes – guaranteed.	Most vehicles that specify 0W-20 (newer Toyotas, Hondas, & GMs), 5W-20 and certain hybrids.	GF-6A, API SP Resource Conserving, SP, SN Plus, SN	
Mobil 1 ⁺	0W-30 Advanced Fuel Economy	760	830	Advanced full synthetic motor oil, engineered to enhance fuel economy and protect for 10,000 miles between oil changes – guaranteed.	Most vehicles that specify 5W-30 or 10W-30.	GF-6A, API SP Resource Conserving, SP, SN Plus, SN	
Mobil 1 ⁺	5W-20	760	830	Advanced full synthetic motor oil, formulated to keep your engine running like new and protect for 10,000 miles between oil changes – guaranteed.	Most vehicles that require 5W-20.	GF-6A, API SP Resource Conserving, SP, SN Plus, SN	
Mobil 1 ⁺	5W-30	760	830	Advanced full synthetic motor oil, formulated to keep your engine running like new and protect for 10,000 miles between oil changes – guaranteed.	Most vehicles that require 5W-30. Corvette approved.	GF-6A, API SP Resource Conserving, SP, SN Plus, SN, Honda/Acura HTO-06	
Mobil 1 ⁺	10W-30	760	830	Advanced full synthetic motor oil, formulated to keep your engine running like new and protect for 10,000 miles between oil changes – guaranteed.	Most vehicles that require 10W-30.	GF-6A, API SP Resource Conserving, SP, SN Plus, SN	
Mobil 1 ⁺	15W-50	1200	1320	Advanced full synthetic motor oil, formulated to keep your engine running like new and protect for 10,000 miles between oil changes – guaranteed.	For high HT/HS applications. Racing and Flat tappet applications.	API SN	A3/B3
Mobil 1 ⁺ High Mileage	0W-20	800	870	Advanced full synthetic motor oil, formulated to prevent leaks and protect engines with over 75,000 miles for 10,000 miles between oil changes – guaranteed.	Most vehicles that specify 0W-20 (newer Toyotas, Hondas, & GMs), 5W-20 and certain hybrids.	GF-6A, API SP Resource Conserving, SP, SN Plus, SN	
Mobil 1 ⁺ High Mileage	5W-20	800	870	Advanced full synthetic motor oil, formulated to prevent leaks and protect engines with over 75,000 miles for 10,000 miles between oil changes – guaranteed.	Most vehicles that require 5W-20.	GF-6A, API SP Resource Conserving, SP, SN Plus, SN	
Mobil 1 ⁺ High Mileage	5W-30	800	870	Advanced full synthetic motor oil, formulated to prevent leaks and protect engines with over 75,000 miles for 10,000 miles between oil changes – guaranteed.	Most vehicles that require 5W-30 or 10W-30.	GF-6A, API SP Resource Conserving, SP, SN Plus, SN	
Mobil 1 ⁺ High Mileage	10W-30	800	870	Advanced full synthetic motor oil, formulated to prevent leaks and protect engines with over 75,000 miles for 10,000 miles between oil changes – guaranteed.	Most vehicles that require 10W-30.	GF-6A, API SP Resource Conserving, SP, SN Plus, SN	
Mobil 1 ⁺ High Mileage	10W-40	800	870	Advanced full synthetic motor oil, formulated to prevent leaks and protect engines with over 75,000 miles for 10,000 miles between oil changes – guaranteed.	Most vehicles that require 10W-40.	API SP, SN Plus, SN	
Mobil 1 ⁺ Truck & SUV	0W-20	760	830	Advanced full synthetic motor oil, designed to protect during tough conditions like towing and hauling for 10,000 miles between oil changes – guaranteed.	Gasoline-powered truck and SUV engines.	GF-6A, API SP Resource Conserving, SP, SN Plus, SN	

Mobil 1™ Truck & SUV	5W-20	760	830	Advanced full synthetic motor oil, designed to protect during tough conditions like towing and hauling for 10,000 miles between oil changes – guaranteed.	Gasoline-powered truck and SUV engines.	GF-6A, API SP Resource Conserving, SP, SN Plus, SN	
Mobil 1™ Truck & SUV	5W-30	760	830	Advanced full synthetic motor oil, designed to protect during tough conditions like towing and hauling for 10,000 miles between oil changes – guaranteed.	Gasoline-powered truck and SUV engines.	GF-6A, API SP Resource Conserving, SP, SN Plus, SN	
Mobil 1™ Turbo Diesel Truck	5W-40	1100	1300	Advanced full synthetic formula designed for modern diesel engines	Most diesel applications including low-emission engine designs.	API CK-4, CJ-4, CI-4 Plus, CI-4 API SN, Caterpillar ECF-2, ECF-3	E7, E9
Mobil 1 Racing™ 4T	10W-40	1150	1260	Advanced full synthetic formula designed specifically for motorcycles where clutch lubrication is also important.	Most motorcycles where 10W-40 is specified.	API SN JASO MA/MA2	
Mobil 1™ V- Twin	20W-50	1560	1770	Advanced full synthetic formula designed specifically for motorcycles where clutch lubrication is also important.	Most motorcycles where 20W-50 is specified, especially V-Twin engines.	API SJ	
Mobil 1 Racing™	0W-30	1770	1940	Advanced full synthetic formula specifically designed to maximize horsepower under race conditions.	Race engines. Not recommended for street use.		
Mobil 1 Racing™	0W-50	1770	1940	Advanced full synthetic formula specifically designed to maximize engine protection under race conditions.	Race engines. Not recommended for street use.		

GM Service Fill Approval	Ford Service Fill Approval	Chrysler Service Fill Approval	Mercedes-Benz Approval	BMW Approval	VW Approval	Porsche Approval
dexos1gen3	WSS-M2C947-A,B1 WSS-M2C962-A1	MS-6395				
	WSS-M2C945-A,B1 WSS-M2C60-A1	MS-6395				
dexos1gen3	WSS-M2C946-A,B1 WSS-M2C961-A1	MS-6395 MS-13340				
	WSS-M2C947-A,B1 WSS-M2C962-A1	MS-6395				
	WSS-M2C945-A,B1 WSS-M2C960-A1	MS-6395				
	WSS-M2C946-A,B1 WSS-M2C961-A1	MS-6395 MS-13340				
dexos2			229.31 / 229.51 / 229.52		511 00	Porsche C40
dexosD			229.71		508 00 / 509 00	Porsche C20
			229.31 / 229.51 / 229.52		504 00 / 507 00	Porsche C30
dexosR						
dexosR						
			229.51/ 229.52	LL-04	504 00 / 507 00	Porsche C30
			229.3 / 229.5	LL-01	502 00 / 505 00	Porsche A40
			229.3			Porsche A40

			229.3 / 229.5	LL-01	502 00 / 505 00	Porsche A40
dexos1gen3	WSS-M2C947-A,B1 WSS-M2C962-A1	MS-6395				
dexos1gen3	WSS-M2C953-A,B1 WSS-M2C963-A1					
	WSS-M2C945-A,B1 WSS-M2C960-A1	MS-6395				
dexos1gen3	WSS-M2C946-A,B1 WSS-M2C961-A1	MS-6395 MS-13340				
	WSS-M2C947-A,B1 WSS-M2C962-A1	MS-6395				
	WSS-M2C945-A,B1 WSS-M2C960-A1	MS-6395				
	WSS-M2C946-A,B1 WSS-M2C961-A1	MS-6395 MS-13340				
dexos1gen3	WSS-M2C947-A,B1 WSS-M2C962-A1	MS-6395				

